



# THE BIGGEST, BADDEST FILTER ON THE BLOCK JUST BECAME THE EASIEST TOO!



## FEATURES

FULL FLOW 1" SERVICE LINES FOR WHOLE HOUSE PERFORMANCE OF UP TO 25 GPM

LONGER LIFE AND LOWER PRESSURE DROP THAN TRADITIONAL 2-1/2" AND 4-1/2" CARTRIDGE FILTERS

BYPASS AND PRESURE RELEASE VALVE ALLOW FOR QUICK FILTER CHANGE WITHOUT REMOVAL FROM PLUMBING - NO TOOLS NECESSARY

UNION CONNECTIONS SIMPLIFY INSTALLATION

UP TO 150 PSI WORKING PRESSURE

TOP DUST COVER KEEPS DUST AND DIRT FROM ACCUMULATING AND GETTING INSIDE HOUSING DURING FILTER CHANGE

FREE STANDING - NO NEED FOR MOUNTING BRACKETS OR WALL ANCHORING

STRAIGHT AND 90° CONNECTIONS PROVIDED





MODEL	DESCRIPTION	TANK DIMENSIONS
MF40	Monstr Flow Filtration System with 1" MPT Fittings	8" X 40"

ABOVE HOUSINGS DO NOT INCLUDE FILTER CARTRIDGES (SEE BELOW)



### Carbon Block Filters for Taste/ Odor Removal & Sediment

General Specifications	CT-03-CB	CT-20-CB	CT-03-CB-AMINE
Micron Rating	3	20	3
Treatment Description	Chlorine / Sediment	Chlorine / Sediment	Chlorine / Sediment / Chloramine
Max Flow Rate / psi drop	25 gpm / 4 psi	25 gpm / 3 psi	25 gpm / 4 psi
Estimated Gallon Capacity	250,000 gallons of water @ 15 gpm with greater than 90% reduction, estimated capacity using 2ppm of free chlorine	150,000 gallons of water with 90% reduction using 2.0 ppm free chlorine at 7 gpm.	50,000 gallons of water with 85% reduction of chloramine @ 7 gpm.



Carbon Block Filters

### Filters for Sediment Removal

General Specifications	CT-2005 - SWMB	CT-2010	CT-1005
Micron Rating	Outer layer 20 / Inner core 5	Outer layer 20 / Inner core 10	Outer layer 10 / Inner Core 5
Treatment Description	Sediment	Sediment	Sediment
Max Flow Rate / psi drop	25 gpm / 4 psi	25 gpm / 4 psi	25 gpm / 4 psi
Surface area vs typical 4.5" x 20" cartridge	2 times as much	6.5 times as much	6.5 times as much
Filter Type	String Wound w/ Melt Blown Core	Dual Gradient / Double Pleated Polyester	Dual Gradient / Double Pleated Polyester



Poly Wound / Melt Blown



Pleated