

| General Specifications | AF10AC-3 | AF12AC-3 | AF13AC-3 | AF14AC-3 |
|--|--------------|--------------|--------------|--------------|
| Filter Media Type | SmartBlend™ | | | |
| Filter Media Capacity (cu ft) | 1.5 | 2.0 | 2.5 | 3.0 |
| Provectr® Tank Size | 10 x 54 | 10 x 54 | 10 x 54 | 16 x 40 |
| Mineral Tank Size | 10 x 54 | 12 x 52 | 13 x 54 | 13 x 65 |
| Service Flow Rate - Continuous (gpm) | 5 | 6 | 8 | 9 |
| Service Flow Rate - Intermittent (gpm) | 7 | 8 | 10 | 11 |
| Backwash Flow Rate (gpm) | 5.0 | 6.0 | 7.0 | 7.0 |
| Gallons Used / Backwash | 100 | 120 | 140 | 140 |
| Space Required (D x W x H) per tank | 10 x 10 x 62 | 10 x 10 x 62 | 10 x 10 x 62 | 16 x 16 x 73 |
| Approximate Shipping Weight (lbs) | 175 | 246 | 280 | 321 |



System Features



- Isobar III Control Valve with meter for precise compressor control
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- Designed for use with constant pressure (variable speed) and jet type pumping systems
- On demand meter for air compressor activation and data / history
- Quiet, high output, oil less air compressor for maximum aeration
- Adjustable Cycle Times
- High backwash flow capability
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- Vortech™ distributor plate