

General Specifications	DS32VN-SQ-3	G10LFMDN-SQ-3	CF10LFMDN-SQ-S3	AF10LFMDN-SQ-S3
Softening Capacity	32,000 grains	N/A	N/A	N/A
Media Type	Softener Resin	N/A	Smart Blend	Smart Blend
Media Capacity	1.0	1.5	1.5	1.5
PROVECTR Tank	N/A	N/A	N/A	16 x 40
Mineral Tank Size	10 x 35	13 x 35	13 x 35	13 x 35
Service Flow Rate	8.0	5.0	5.0	5.0
Backwash Rate	2.0	7.0	7.0	7.0
Space Required	16 x 26 x 43	13 x 13 x 43	13 x 13 x 43	40 x 53 x 56
Approximate Shipping Weight (lbs)	78	140	146	140

Note: Caution should always be used in sizing filters! Always choose a unit by first satisfying the Backwash requirement. Use of a flow control in the Service Line is highly recommended. Consult the factory or your field sales person with questions. Oxyclean can be added to any existing PROVECTR or PROVECTR PLUS system.



System Features

- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- Adjustable Cycle Times
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- Filters come standard with dome hole and natural color
- All tanks feature Vortech distributor plate
- Standard brine tank size 16" X 33"